





Anti-Spatter for Welding (W506)

This product is free of silicone substance, and it's ideal for professional uses but can also be used for do-it-yourself uses. This spray prevents the formation of corrosions, and it protects from humidity and prevents seize.



ANTI-SPATTER FOR WELDING - A product made of film forming synthetic polymers. Due to their special features, it prevents the seizure of welding spatter to any surface. The film also prevents oxidation and corrosion caused by chemicals. It is suitable for autogenous, electric and inert-gas welding. The compound is free of silicon substances.

Technical specifications:

Barcode	EAN: 8034108890517
Quantity	400 ml
Box / Case	12 Pz.
Aspect	Tin-Plate can containing under pressure fluid
Colour	straw yellow
Odour	Odorless
Relative density	At 20°C 0,54 ÷ 0,58 g/ml
Flash point	Und. 0° C extremely flammable
Pressure at 20°C	3/5 bar
Vapor pressure	< 0,01 hPa a 20°C
Vapor density(air=1)	9-12
Viscosity at 50°C	(ASTM D 445) 11 ÷ 24 cst
Silubility	Insoluble in water
Autoignition temperature	>400°C(dry residual)
Corrosion on copper	(ASTM D 130): 1

HOW TO USE Before applying the product, carefully clean the torch from existing waste. Shake the can well before use and make the first vacuum spray if the can is new. Dispense the product at a distance of 20-30 cm from the mouth of the torch and on the edges of the surface to be welded, keeping the cylinder in a vertical position. Aspirate locally before starting the weld. Do not spray an excessive amount of product and do not dispense the product near the working torch. Keep the cylinder away from heat sources and from the working torch.

MODALITY OF STORAGE

Before using: stock the product in a dry location and don't stock it with a temperature under 0°C and over 45°C, after the use, keep containers closed. In the original package, the product can be conserved for 24 months (warranty). The product doesn't expire.

After the first usage: conserve in a fresh and dry location, away from hot spring. Keep out of reach of children.

This information, even if reliable, must be considered only approximate. We are not responsible for the wrong use of the product, or the violation of any license. Before using, the users should verify the suitability of the product for its specific use.





Ambro-Sol - 25020 Cigole (BS) Italy - www.ambro-sol.com - info@ambro-sol.com